WIRELESS GO **I** TX

TRANSMITTER FOR THE WIRELESS GO II

The Wireless GO II TX is an extremely versatile and ultra-compact wireless transmitter that's perfect for interviews, filmmaking and wide range of content creation. Simply clip it onto your talent and record with the high-quality built-in microphone, or attach to a belt or boom arm and run a lavalier into the 3.5mm analog input. You can capture over 40 hours of on-board recordings on the transmitter itself, or transmit the audio via RØDE's cutting-edge Series IV 2.4GHz wireless transmission with up to 200m (line of sight) range.

Note: This product requires a RØDE Series IV RX (receiver) to operate, such as the Wireless GO II RX, Wireless ME RX, RØDECaster Pro II, RØDECaster Duo or Streamer X.

- Versatile wireless transmitter for the RØDE Series IV wireless systemExtended frequency response
- Series IV 2.4GHz digital transmission, 128-bit encryptions
- High-quality, built-in omnidirectional microphone
- On-board recording over 40 hours of internal memory

- 3.5mm TRS analog input for connecting lavalier and VideoMics
- In-built rechargeable lithium-ion battery – up to 7 hours battery life
- 200m transmission range (line-of-sight)
- Requires a RØDE Series IV receiver to operate (including Wireless GO II RX, Wireless ME RX, RØDECaster Pro II, RØDECaster Duo or Streamer X)









ACOUSTIC & ELECTRICAL SPECIFICATIONS

Acoustic Principle:	Pre-polarised pressure transducer
Polar Pattern:	Omnidirectional
Frequency Range:	50Hz – 20kHz
Maximum SPL (Mic):	100 dB SPL (1kHz @ 1m) dBu
Maximum Input Level (3.5mm):	-20dBV
Microphone Preamp Gain:	20dB
Equivalent Noise Level:	22dBA (A-weighted)
Power Requirements:	In-built rechargeable lithium-ion battery charged via USB 5V, 0.3A
Operating Time:	Up to 7 hours
Analog Inputs:	3.5mm TRS (lavalier microphone input)
Analog Outputs:	3.5mm TRS
Transmission Range:	200m (line-of-sight)
Computer Connectivity:	USB Type-C
Operating System Requirements:	macOS 10.11 above Windows 7 and above



MECHANICAL SPECIFICATIONS

WHATS IN THE BOX

Weight (grams):	30
Dimensions (millimetres):	Legth: 44 Width: 45.3 Height: 18.3
Included Accessories:	2 x Furry Windshields 1 x SC22, 30cm USB-C to USB-C cable



Wireless GO II Transmitter (TX)







Furry Windshields

SC22

DIMENSIONS



POLAR PATTERN



18.5mm

FREQUENCY RESPONSE

