

对比表：后级

	型号	Performer s1200	Performer s900	Performer s800	Performer m1000
通道		2	2	2	1
桥接模式		○	○	●	○
线路输入	XLR (平衡)	●	●	●	●
	RCA (非平衡)	●	●	○	○
线路直通	XLR (平衡)	○	○	●	●
参数	输入灵敏度	10.5 dB	8 dB	6 dB	12.5 dB
	输出阻抗 (20 Hz - 20 kHz)	< 0.04 Ω	< 0.035 Ω	< 0.031 Ω	< 0.031 Ω
	放大	26 dB	26 dB	26 dB	26 dB
	阻尼系数 (1 kHz, 8 Ω)	> 290	> 280	> 300	> 280
	频率范围	10 Hz - 80 kHz	10 Hz - 80 kHz	10 Hz - 80 kHz	10 Hz - 80 kHz
	THD (1 kHz, 8 Ω)	< 0.04 %	< 0.04 %	< 0.03 %	< 0.03 %
	噪声	-123 dB	-123 dB	-123 dB	-123 dB
输出功率	2 Ω (有效值)	2 × 550 W	2 × 420 W	○	1000 W
	4 Ω (有效值)	2 × 520 W	2 × 370 W	2 × 285 W	750 W
	8 Ω (有效值)	2 × 300 W	2 × 200 W	2 × 185 W	420 W
	输出电压 (有效值)	54.6 V	40.2 V	35 V	64.6 V
	输出电压 (有效值)	160 V	112 V	74 V	180 V
	8 Ω (桥接模式, 有效值)	○	○	450 V	○
电源	环形线性电源变压器	●	●	●	●
	筛分容量	70,000 μF	48,000 μF	40,800 μF	100,000 μF
	最大功耗	1440 VA	900 VA	875 VA	1375 VA
	空闲功耗	50 W	20 W	40 W	50 W
	待机功耗	< 0.3 W	< 0.3 W	< 0.3 W	< 0.3 W
AMP CTL	12V 触发	●	●	●	●
尺寸及重量	宽 × 高 × 深 (包括支脚)	278 × 205 × 345mm 11" × 8" × 13.6"	278 × 114 × 345mm 11" × 4.5" × 13.6"	278 × 100 × 345mm 11" × 4" × 13.6"	278 × 205 × 345mm 11" × 8" × 13.6"
	重量	25.1kg / 55.3 lbs	14.6kg / 32.2 lbs	14kg / 30.9 lbs	24.8kg / 54.7 lbs