

# RØDELink Newsshooter Kit

## AUSTRALIA

107 Carnarvon st, Silverwater NSW 2128 Australia  
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

## USA

PO Box 91028, Long Beach CA 90809-1028  
Ph: +1 562 364 7400 Fax: +1 888 412 4664



## Features

- Includes Transmitter (XLR adaptor) and Receiver (camera or beltback mount)
- XLR (w/P48) input, 3.5mm input and headphone output on transmitter
- Series II 2.4GHz digital transmission
- 128-bit encrypted signal
- Up to 100m range\*
- One touch pairing
- OLED digital display
- AA Battery or USB Power
- NP-F battery option on transmitter
- Designed and made in Australia

## General System Specs

Transmission type	2.4GHz fixed frequency agile system
System dynamic range	112dB
Range (distance)	100m*
Frequency range	35Hz - 22kHz
Maximum output level	1v rms (2.8v p-p)
Max input signal level	1v rms (2.8v p-p)
Max latency	4ms

## Receiver (RX-CAM)

Power source	2 x AA battery and USB Power
Antenna	Internal
Output connection	3.5mm TRS jack socket – dual mono with thread lock
Output impedance	300 Ω
Dimensions	111mm H x 65mm W x 52mm D
Weight	190gm

## Transmitter (TX-XLR)

Power source	2 x AA, NP-F battery and USB Power
Antenna	Internal
Input connection	XLR with lock, 3.5mm TRS jack socket with thread lock
Input power	XLR - P48 phantom, 3.5mm - 4V 'plug in' power
Input impedance	10k ohms
Dimensions	120mm H x 45mm W x 45mm D
Weight	222gm

**RØDE**  
MICROPHONES

\* range estimations based on optimal environment